

Technical Data Sheet



Teak Oil

Product description

Type

This product is based on vegetable oil.

Features and benefits

The penetration properties provides a very good protection to teak surfaces.

Recommended use

Designed to protect the teak deck from oxidation and usual problems caused by environmental agents.

Packaging (typical)

	Volume (litres)	Size of containers (litres)
Teak Oil	0.5 / 5	0.5 / 5

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Product data

Colours	straw coloured
Generic type	alkyd
Solids	20 ± 2 volume%
Flash point	Closed cup: 47°C (116,6°F)
Flash point	42 °C
VOC	650 g/l US EPA method 24

Application data

The product can be applied by

Brush: Brush designed for stains.

Product mixing ratio (by volume)

Single pack

Thinner

Jotun Thinner No. 2 / JOTUN White Spirit

Technical Data Sheet

Teak Oil



Jotun Protects Property

Drying times

Relative Humidity (RH) 50 %

Substrate temperature

Hard dry

Dry to over coat, minimum

10 °C	23 °C	40 °C
1 h	1 h	1 h
1 h	1 h	1 h

Directions for use

Surface preparation

On coated surfaces remove loose varnish, weathered wood and loose wood fibre. Teak surfaces with stain and heavy miscolouration, wash with recommended Jotun Yachting detergent. For best result, the substrate should be clean, dry and free from any contamination.

Pretreatment

Rinse well with fresh water. Clean with Teak Cleaner.

Finish coat

Apply one coat. After 15 minutes remove the exceeding oil with a dry and clean cloth. Damaged or very dry wood might need more than one coat, repeat the process.

Remarks

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

Teak Oil 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Technical Data Sheet

Teak Oil



Jotun Protects Property

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. For your nearest local Jotun office, please visit our website at www.jotun.com.